





A Guide To Footings & Foundations

Design Extracts for Decks, Pergolas and Fencing.



Contents

A Guide To Footings And Foundations Revised -1/7/07

Definition	Page 3
Design Principles	Page 3
Footing Failure	Page 3
Engineer	Page 4
Foundations	Page 5
Pad Footings	Page 5
Strip Footings	Page 6
Pier and Beam Reinforced Steel Footings	Page 7
Props and Hoarding	Page 8
Underpinning	Page 9
Safety In The Workplace	Page 10

Definitions

Foundations:

'Foundations' refers to the natural ground and its structure such as sand, clay, rock or mixed materials.

Footings:

'Footings' is the term used to describe the designed and built portion of the sub structure. This can be constructed of brick, concrete or other purposely designed materials. For larger structures footings may require a structural engineers plan including council inspections and approval during the course of the project. For projects of this scale a Development Application should be lodged with your local building approval body.

Design Principles

Pergolas, decks and garden structures

The object of footings for timber pergolas, decks and other garden structures is to transfer the load of the structure directly to the foundations. The footings should be adequately designed to support the weight of the load, and the strength of the foundation material. For this reason the same load may require different footings depending on the foundation material.

'Pad' or 'Mass' concrete footings refer to a cubic concrete footing without reinforcement steel. The footing size will vary depending on the strength of the foundation material.

Retaining Walls

Retaining wall footings need to be designed to counter the lateral force exerted on the wall by the soil it is retaining. For this reason, the footing and wall should be designed as one piece in an 'L' shape. *see illustration*

The footing should contain reinforcement steel and starter bars. The starter bars should protrude out of the concrete at spacings roughly 1m or equal to the holes in the blocks.

The bottom of the `L' is to sit under the load to pull the wall against the lateral forces.

Strip Footings

are not only to support the structure but also to combat lateral forces. Th

Foundation Material	Bulking
Sand	1m3 = 1m3
Rock	1m3 = 1.5m3
Clay	1 m3 = 2.5m3

Footing Design	Suitability
Pad (mass concrete)	Fencing, Decks, Pergolas, Carports, Garden Structures
Strip Footings (reinforced concrete)	Retaining Walls, Masonry Fencing, Housing and Small Buildings
Pier & Beam (reinforced concrete)	For larger structures, double brick, concrete, design and build to Engineers Details.









Notes;

- 1. This table is extracted from AS 1684 2006 Residential Timber Framed Construction Standards and assumes the building practice contained within that standard.
- Roof load is calculated at zero, ie; no roof or wall loads are taken into account. Assumes a maximum floor mass of 40 kg/m2.
- 3. Joists crippled over supports shall be calculated as single spans.
- 4. NS = not suitable

This publication is produced by the Timber and Building Materials Association, in conjunction with the Timber Development Association NSW and with assistance from the FWPRDC. The FWPRDC is jointly funded by the forest and wood products industry and the Australian Government.

Important notice;

This guide has been assembled by All Day Fencing. Successful design and construction depends on numerous factors outside the scope of this publication. While all care has been taken in the assembly of this information, All Day Fencing accepts no responsibility, liability loss or damage resulting from work performed based on information contained in this publication/guide whether as a result of All Day Fencing negligence or otherwise.

Tool Job Guide		
A Guide to The Right Tool For Every Job		
Stage	Suggested Tools	
Demolition	Handtools; Sledge Hammer, Lump Hammer, Claw Hammer, Handsaw, Pinchbar, Crowbar, Screwdrivers.	
	Power Tools; Demolition Hammer, Demolition saw, Jackhammer, Chainsaw, Circular Saw.	
Excavation	Handtools; Trenching spade, Long handle wide mouth shovel, Long handle shovel, Mattick, Crowbar, Post hole digger, Wheelbarrow.	
	Power Tools; Diesel post hole digger, Jackhammer, Core drill, Hammer drill.	
Concreting	Handtools; Wide mouth shovel, short handle shovel, wheelbarrow, straight edge, timber float, timber trowel, steel trowel, broom, bucket, hose.	
	Concrete pump, vibrator, power screed	
Carpentry	Handtools; Square, pencil, saw, bevel, spirit level, claw hammer, punch, screwdrivers, shifting spanner, wood chisels, builder line, clamps, sandpaper	
	Power Tools; Circular saw, jig saw, drill, hammer drill, router, orbital sander, belt sander, electric planer	
Brickwork	Handtools; Brick trowel, lump hammer, bolster, plugging chisel, spirit level, profiles, bricklayers line	
	Power Tools;	
Steelwork	Handtools;	
	Clamps, file, ball pen hammer, vice, boltcutters, pipe bender, hacksaw	
	Power Tools;	
Glazing/Plastering	Handtools; Claw hammer, wood chisel, broad knife, steel trowel, putty knife, sanding block	
	Power Tools; Orbital sanding	

Safety First	
Symbol	Definition
Boots	Steel Cap Boots are Required
Earmuffs	Earmuffs are Required
Safety Glasses	Safety Glasses must be worn
Hardhat	
Hoarding	Hoarding should be erected
Safety Fencing	
Signage	